EWHB Electric Wash Down Unit Heaters Ordering Guide

Reznor's EWHB is a corrosion-resistant electric unit heater engineered for demanding commercial and industrial environments where washdown procedures, moisture, and harsh conditions are common. Featuring stainless-steel construction, watertight controls, and durable components, the EWHB delivers reliable comfort while standing up to frequent cleaning and challenging operating conditions.

Benefits

- Corrosion-resistant design with stainless-steel housing, louvers, grille, and mounting hardware for long service life in wet environments
- Designed for washdown applications with watertight controls and a NEMA 4X electrical enclosure that helps protect internal components
- Flexible installation with included stainless-steel swivel mounting bracket for wall or ceiling mounting
- Durable performance with sealed tubular heating elements, stainless-steel fins, and a lubricated enclosed motor
- Adjustable outlet louvers allow heat to be directed where it is needed most
- Simplified operation with integrated thermostat, 24V control circuit, and optional watertight disconnect and fan switches

Applications

Food & Beverage Processing

- Food production facilities
- Beverage processing plants
- Packaging areas
- Commercial kitchens

Commercial & Industrial

- Washdown areas
- Manufacturing facilities
- Water and wastewater treatment plants
- Agricultural buildings
- Processing plants
- Maintenance facilities
- Equipment wash bays

Specialty Environments

- High-humidity spaces
- Corrosive environments
- Indoor industrial work areas requiring frequent cleaning and sanitation



Ordering Details

Factory-Installed Options

Model	Size (kW)	Fan Relays & Switches	Factory-Installed Disconnect	Pilot Light	Voltage/Phase/Hertz Options
EWHB	3 5 7 10 15 20 25 30 38	**BF4B**-Unit mounted fan switch waterproof	**BA5A**-Watertight 40A unit mounted disconnect	**BB**-Pilot light unit mounted (Power-on indicator)	**AK2**-208/1/60 [1] **AK3E**-208/240/1/60 [2] **AK5**-208/3/60 [3] **AK6E**-240/3/60 [4] **AK7E**-480/3/60 **AK8E**-600/3/60

[1] Not available for the following sizes: 10, 15, 20, 25, 30, 38
[2] Not available for the following sizes: 15, 20, 25, 30, 38
[3] Not available for the following sizes: 20, 25, 30, 38
[4] Not available for the following sizes: 20, 25, 30, 38

Field-Installed Options

Internal Unit Thermostat	**IC18**-Unit mounted watertight
Wall Thermostat	**CL5A**-Vertical SPST line voltage 22A max @ 240/1 (5kW) 45°-75°

Call your REZNOR® Rep at 800.695.1901 to find a product that works for you.
Visit reznorhvac.com for more information on the REZNOR® product line.

© 2026 Reznor LLC. All Rights Reserved.

REZNOR®