EXUB Electric Explosion-Proof Heater Ordering Guide

Reznor's EXUB is an explosion-resistant electric unit heater engineered for hazardous commercial and industrial environments where reliability and performance are critical. Designed to meet demanding hazardous-location requirements, the EXUB provides dependable comfort heating and freeze protection in facilities where explosive gases, vapors, dust, or fibers may be present.

Benefits

- Long-life heat exchanger core maximizes heat transfer while delivering excellent resistance to corrosion and harsh operating conditions
- Explosion-resistant, thermally protected fan motor provides dependable performance in hazardous environments
- Adjustable aluminum louvers allow airflow to be directed where heat is needed most
- Designed for serviceability with a removable heat exchanger assembly and replaceable high-limit controls

Approved Locations

- Class I, Divisions 1 and 2, Groups C and D
- Class II, Divisions 1 and 2, Groups F and G
- Temperature code: T3B (5 to 30kW), T3A (3/35kW)
- Class I, Zones 1 & 2 , Groups IIA & IIB, T3

Applications

Hazardous Industrial Facilities

- Oil and gas processing facilities
- Petrochemical plants
- Refineries
- Chemical manufacturing facilities
- Paint and solvent storage areas

Heavy Industrial

- Power generation facilities
- Mining operations
- Pulp and paper plants
- Metal processing facilities
- Industrial warehouses
- Maintenance and utility buildings

Freeze Protection & Specialty Applications

- Pump houses
- Hazardous storage areas
- Process control rooms
- Equipment shelters
- Remote industrial facilities



Ordering Details

Factory-Installed Options

Model	Size (kW)	Internal Unit Thermostat	Voltage/Phase/Hertz Options	Control Voltage	Factory-Installed Disconnect
EXUB	3 5 7 10 15 20 25 30 35	**IX34**-50°-90° F explosion proof	**AK2**-208/1/60 [1] **AK3E**-208/240/1/60 [2] **AK5**-208/3/60 [3] **AK6E**-240/3/60 [4] **AK7E**-480/3/60 **AK8E**-600/3/60	**BT1**-24V	**BAX1**-Hazard environment

[1] Not available for the following sizes: 10, 15, 20, 25, 30, 35
[2] Not available for the following sizes: 15, 20, 25, 30, 35
[3] Not available for the following sizes: 20, 25, 30, 35
[4] Not available for the following sizes: 20, 25, 30, 35

Field-Installed Options

Unit Suspension Support	**CK20**-Horizontal arm for post attachment **CK25**-Pipe hanger brackets **CK26**-Wall mounting arm with flange **CK27**-Block wall mounting arm with z supports
Wall Thermostat	**CX1**-Explosion proof wall 40°-80° F

Call your REZNOR® Rep at 800.695.1901 to find a product that works for you.
Visit reznorhvac.com for more information on the REZNOR® product line.

© 2026 Reznor LLC. All Rights Reserved.

REZNOR®