ECR Ceiling Recess-Mounted Heater Ordering Guide

ECR is a recessed ceiling-mounted electric heater designed to provide supplemental warmth and improved air circulation without disrupting the appearance of occupied spaces. Its low-profile design, quiet operation, and downward airflow make it an ideal solution for commercial, institutional, and residential applications where comfort and aesthetics are equally important.

Benefits

- Discreet recessed ceiling design helps deliver comfort without occupying valuable wall or floor space
- Help improve occupant comfort by circulating warm air that naturally accumulates near ceilings back into the occupied zone
- Attractive architectural appearance with a low-profile grille and choice of white or almond finish
- Reliable performance with an enclosed lifetime-lubricated fan motor and durable stainless-steel tubular heating elements with aluminum fins
- Flexible electrical configurations with a wide range of voltage and phase options to meet project requirements

Applications

Commercial & Institutional

- Retail stores
- Hotels and hospitality facilities
- Office buildings
- Showrooms
- Schools and universities
- Healthcare and medical facilities
- Exhibition halls
- Sports and recreation facilities
- Churches and places of worship
- Transportation terminals
- Warehouses and distribution centers
- Food and beverage facilities

Residential

- Apartments and condominiums
- Entryways and common areas
- Home additions and renovations
- Supplemental heating applications



Ordering Details

Factory-Installed Options

Model	Size (kW)	Cabinet Color	Factory-Installed Disconnect	Fan Relays & Switches	Internal Unit Mounted Thermostat	Voltage/Phase/ Hertz Options	Factory-Installed Control Voltage
ECR	2 3 4 5	**HK1**-White **HK2**-Almond	**BA14**-40A unit mount 3 pole **BA15**-80A unit mount 3-pole **BA21**-20A unit mount 1-phase 277V	**BB12**-24V terminal for remote fan (switch not included)	**IC15**-Single-stage tamperproof	**AK2**-208/1/60 **AK3E**-208/240/1/60 **AK4**-277/1/60 **AK5**-208/3/60 **AK6E**-240 /3/60 **AK7E**-480/3/60 **AK8E**-600/3/60 **AK9E**-480/1/60 **AK10**-575/1/60 **AK34**-347/1	**BT1**-24V Control relay with transformer **BT2**-120V Control relay with transformer

Field-Installed Options

Wall Thermostats	**CL1A**-Single-stage 40°-80° F 24V WR IE-30 **CL5**-Single-stage 50°-80° F 115V
Unit Control Relay	**IR24**-Control relay for 24V signal by others

Call your REZNOR® Rep at 800.695.1901 to find a product that works for you.
Visit reznorhvac.com for more information on the REZNOR® product line.

© 2026 Reznor LLC. All Rights Reserved.

REZNOR®